

<b>Modello</b>	<b>Portata [Kg]</b>	<b>Velocità [m/min.]</b>	<b>Kw</b>	<b>Tiri di catena</b>	<b>A</b>	<b>B</b>	<b>B1</b>	<b>Ø C</b>	<b>C1</b>	<b>C2</b>	<b>C3</b>	<b>D</b>	<b>D1</b>	<b>E</b>	<b>F</b>	<b>Ø G</b>	<b>Ø G1</b>	<b>G2</b>	<b>H</b>	<b>H1</b>	<b>H2</b>	<b>H3</b>	<b>L</b>	<b>S</b>	<b>Peso [Kg]</b>
1000WR12	1000	13,5	3	1	590	125	350	10	12	34	28	280	40	54	25	40	50	37	200	320	335	655	230	*	98
1000WR31	1000	3-12	0,7-3	1	590	125	350	10	12	34	28	280	40	54	25	40	50	37	200	350	335	685	230	*	83
1500WR8	1500	8	3	1	590	125	350	10	12	34	28	280	40	54	25	40	50	37	200	320	305	625	230	*	98
1500WR28	1500	2-8	0,7-3	1	590	125	350	10	12	34	28	280	40	54	25	40	50	37	200	350	305	655	230	*	98
1500WR12	1500	13,5	3	1	590	125	350	11	13,2	37,4	31	280	40	54	25	40	50	37	200	320	335	655	230	*	98
1500WR31	1500	3-12	0,7-3	1	590	125	350	11	13,2	37,4	31	280	40	54	25	40	50	37	200	350	335	685	230	*	98
2000WR8	2000	8	3	1	590	125	350	11	13,2	37,4	31	280	40	54	25	40	50	37	200	320	335	655	230	*	105
2000WR28	2000	2-8	0,7-3	1	590	125	350	11	13,2	37,4	31	280	40	54	25	40	50	37	200	350	335	685	230	*	98
2500WR8	2500	8	3	1	625	125	350	11	13,2	37,4	31	280	40	54	25	40	50	37	200	320	335	655	230	*	98
2500WR28	2500	2-8	0,8-3,5	1	625	125	350	11	13,2	37,4	31	280	40	54	25	40	50	37	200	350	335	685	230	*	98