

Modèle	Capacité [Kg]	Vitesse [m/min.]	Kw	Nombre de chaîne	A	A1	B	B1	B2	Ø C	C1	C2	C3	D	D1	E	F	Ø G	G1	H	H1	H2	H3	L	Ø R	S	Ø T	Poids [Kg]
1000WR12	1000	13,5	3	1	650	95	54	176	342	10	12	34	28	280	175	32	34	50	37	200	320	335	655	230	80	*	24	120
1000WR312	1000	3-12	0,7-3	1	650	95	54	176	342	10	12	34	28	280	175	32	34	50	37	200	350	335	685	230	80	*	24	98
1500WR8	1500	8	3	1	650	95	54	176	342	10	12	34	28	280	175	32	34	50	37	200	320	305	625	230	80	*	24	120
1500WR28	1500	2-8	0,7-3	1	650	95	54	176	342	10	12	34	28	280	175	32	34	50	37	200	350	305	655	230	80	*	24	120
1500WR12	1500	13,5	3	1	650	95	54	176	342	11	13,2	37,4	31	280	175	32	34	50	37	200	320	335	655	230	80	*	24	120
1500WR31	1500	3-12	0,7-3	1	650	95	54	176	342	11	13,2	37,4	31	280	175	32	34	50	37	200	350	335	685	230	80	*	24	120
2000WR8	2000	8	3	1	650	95	54	176	342	11	13,2	37,4	31	280	175	32	34	50	37	200	320	335	655	230	80	*	24	120
2000WR28	2000	2-8	0,7-3	1	650	95	54	176	342	11	13,2	37,4	31	280	175	32	34	50	37	200	350	335	685	230	80	*	24	125
2500WR8	2500	8	3	1	685	95	54	176	342	11	13,2	37,4	31	280	175	32	34	50	37	200	320	335	655	230	80	*	24	115
2500WR28	2500	2-8	0,8-3,5	1	685	95	54	176	342	11	13,2	37,4	31	280	175	32	34	50	37	200	350	335	685	230	80	*	24	125